


Nautilus Marine Gear Oil

Marine Gear Oil for manual shift transmissions



Nautilus Marine Gear Oil is a high quality, extreme pressure lubricant for the protection of marine transmission systems.

Applications

- Marine transmission systems
- Outboard gear boxes with manual shift especially:
MERCURY EVINRUDE JOHNSON
MARINER CHRYSLER ISUZUKI
YAMAHA
- Stern drive gearboxes requiring an EP Gear Oil SAE 90

Performance Specifications

Nautilus Marine Gear Oil satisfies the requirements of major manufacturers specifying an extreme pressure gear oil.

It exceeds the following industry standards:

API GL-4

Available Viscosities

SAE 90

Health & Safety

Nautilus Marine Gear Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

Protect the environment

Take used oil to an authorised used oil collection point. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Typical Physical Characteristics

Nautilus Marine Gear Oil	
SAE Viscosity Grade	90
Kinematic Viscosity @ 40°C cSt 100°C cSt (IP 71)	184.0 16.9
Density @ 15°C kg/l (IP 365)	0.904
Flash Point °C (PMCC) (IP 34)	191
Pour Point °C (IP 15)	-18

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.