

Shell Nautilus Premium Inboard

Four stroke premium inboard oil



Nautilus Premium Inboard is a high performance lubricant manufactured to provide superior protection of inboard four-stroke engines.

Applications

- **All gasoline and diesel four-stroke inboard engines.**

Performance Features and Benefits

- **Very good engine protection**
In all conditions and with all the engines used for inboard applications.
- **Universal Coverage**
Lubricates both diesel and gasoline engines allowing one oil to be stocked for a variety of different vessels.
- **Peace of mind**
Extensive Shell experience allows leisure boating with maximum confidence in the protection of the engine.

Specification and Approvals

Nautilus Premium Inboard exceeds the requirements of all major inboard engine manufacturers and the following industry standards:

API CG-4/CF/SJ,
ACEA A2, B2, E2
VOLVO VDS

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet that can be obtained from your Shell representative.

Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Physical Characteristics

Nautilus Premium Inboard			
SAE Viscosity grade			15W-40
Kinematic Viscosity		ASTM D 445	
	at 40°C	mm ² /s	105
	at 100°C	mm ² /s	14.6
Viscosity Index		ISO 2909	143
Density at 15°C	kg/m ³	ASTM D 4052	890
Flash Point COC	°C	ISO 2592	220
Pour Point	°C	ISO 3016	-30

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.