

Shell Donax TM

Automatic transmission fluid



Donax TM is a high quality automotive transmission, power steering and hydraulic oil mainly used for heavy-duty vehicles working in an 'off-road' environment.

Applications

- Powershift and Industrial torque convertors
- Applications calling for a GM Type 'A' Suffix 'A' performance fluid
- Automatic transmission and power steering fluid used in heavy trucks and off-road vehicles
- Hydraulic oil for certain off-road applications

Performance Features and Benefits

- Oxidation & thermal stability
- Dispersancy
- Friction retention
- Shear stability
- Anti-wear & EP performance

Specification and Approvals

General Motors	Type 'A' Suffix 'A'
Mercedes-Benz Sheet	236.2, 236.5
MAN	339 Type A

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet which can be obtained from your Shell representative.

Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Physical Characteristics

Donax TM			
Kinematic Viscosity		ISO 3104	
at 40°C	mm ² /s		40.0
at 100°C	mm ² /s		7.5
Viscosity Index		ISO 2909	157
Density at 15°C	kg/m ³	ISO 12185	880
Flash Point COC	°C	ISO 2592	170
Pour Point	°C	ISO 3016	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.